



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

## Introducing the Grizzly Model G0538 Bench Top Oscillating Spindle Sander



### **MACHINE HIGHLIGHTS (see Machine Data Sheet for full specifications)**

- 1/3 HP, 110V, single-phase motor.
- Easily smooths curved edges and fits on space-limited work benches.
- Spindle oscillates at 72 SPM with 5/8" stroke length.
- Extra large 20" x 14" table with storage underneath for inserts, sanding drums, and sleeves.
- Comes with six 4 1/2" tall sanding drums, three 80 grit sleeves, three 150 grit sleeves, six inserts, and two spindle changing wrenches.
- Also features an ON/OFF paddle switch with a lockout key and a 2 1/2" dust port.

The Model G0538 Bench Top Oscillating Spindle Sander is available for \$149.95. As with all Grizzly products, the Model G0538 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit [www.grizzly.com](http://www.grizzly.com).



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0538 1/3 HP OSCILLATING SPINDLE SANDER

### Product Dimensions:

Weight..... 34 lbs.  
 Length/Width/Height..... 20 x 14 x 11-1/2 in.  
 Foot Print (Length/Width)..... 20 x 14 in.

### Shipping Dimensions:

Type..... Cardboard  
 Content..... Machine  
 Weight..... 37 lbs.  
 Length/Width/Height..... 22 x 16 x 18 in.

### Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz  
 Minimum Circuit Size..... 10 amp  
 Switch..... Paddle with Locking Tab  
 Switch Voltage..... 110V  
 Cord Length..... 9 ft.  
 Cord Gauge..... 18 gauge  
 Plug Included..... Yes  
 Included Plug/Outlet Type..... 5-15

### Motors:

#### Main

Type..... Universal  
 Horsepower..... 1/3 HP  
 Voltage..... 110V  
 Prewired..... 110V  
 Phase..... Single  
 Amps..... 4A  
 Speed..... 1725 RPM  
 Cycle..... 60 Hz  
 Number Of Speeds..... 1  
 Power Transfer ..... Direct  
 Bearings..... Sealed and Permanently Lubricated

### Main Specifications:

#### Table Info

Table Width..... 14 in.  
 Table Length..... 20 in.  
 Table Thickness..... 1 in.  
 Table Opening..... 3-1/2 in.  
 Table Inserts..... 11/16, 15/16, 1-3/16, 1-21/32, 2-3/16, 3-3/16 in.

**Spindle Info**

Spindle Diameters..... 1/2, 3/4, 1, 1-1/2, 2, 3 in.  
 Spindle Lengths..... 4-1/2 in.  
 Spindle Speed..... 1725 RPM  
 Spindle Oscillations..... 72 SPM  
 Stroke Length..... 5/8 in.  
 Arbor Size..... 1/2 in.  
 Total Arbor Length..... 4-1/2 in.

**Construction**

Base Construction..... Plastic  
 Table Construction..... Particle Board with Plastic Laminate  
 Frame Construction..... Plastic  
  
 No. Of Dust Ports..... 1  
 Dust Port Size..... 2-1/2 in.

**Other Specifications:**

Country Of Origin ..... China  
 Warranty ..... 1 Year  
 Serial Number Location ..... On Front  
 Assembly Time ..... 20 minutes

**Features:**

- Paddle On/Off Switch with Lock
- Six 4-1/2 in. Tall Sanding Drums
- Compact Size for Easy Storage
- Three 80 gr. Sleeves (1/2", 1" and 2")
- Three 150 gr. Sleeves (3/4", 1-1/2" and 3")
- Six Table Inserts