



CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G0640X 17" Wood/Metal Bandsaw



MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 2 HP, variable speed motor, operates on 220V single-phase power source.
- Precision ground cast iron fence with extruded aluminum resaw fence attachment.
- Ball bearing blade guides with rack-and-pinion blade guide elevation adjustment.
- Fully balanced, heavy-duty cast iron wheels.
- Can be set up to cut wood or metal with a simple conversion and blade change.
- Packed with other great features like dual 4" dust ports, quick release blade tension, and blade tracking window.

The Model G0640X 17" Wood/Metal Bandsaw is available for \$1,595.00. As with all Grizzly products, the Model G0640X is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0640X 17" METAL/WOOD BANDSAW W/INVERTER MOTOR

Product Dimensions:

Weight..... 378 lbs.
Length/Width/Height..... 32 x 32 x 73 in.
Foot Print (Length/Width)..... 27 x 17-3/4 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 416 lbs.
Length/Width/Height..... 31 x 20 x 81 in.

Electrical:

Minimum Circuit Size..... 15 amp
Switch..... ON/OFF Push Button with Locking Key Switch
Switch Voltage..... 220V
Cord Length..... 6 ft.
Cord Gauge..... 14 guage
Plug Included..... No

Motors:

Main

Type..... Induction
Horsepower..... 2 HP
Voltage..... 220V
Prewired..... 220V
Phase..... Three
Amps..... 8A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Operation Info

Blade Speeds..... Variable 100 - 3600 FPM
Std. Blade Len..... 131-1/2 in.
Blade Size Range..... 1/8 - 1 in.

Cutting Capacities

Cutting Height..... 12 in.
Cutting Capacity Left Of Blade..... 16-1/4 in.

Construction

Table Construction.....Precision Ground Cast Iron
 Wheel Construction Upper.....Fully-Balanced Cast Iron
 Wheel Construction Lower.....Fully-Balanced Cast Iron
 Tire Material..... Rubber
 Body Construction.....Steel
 Base Construction.....Steel
 Wheel Cover Construction..... Steel
 Paint..... Power Coated

Other

Wheel Size..... 17 in.
 Blade Guides Upper..... Ball Bearing
 Blade Guides Lower..... Ball Bearing
 Mobile Base..... G7314Z

Table Info

Table Tilt..... -5 to 45 deg.
 Table Size Length..... 23-5/8 in.
 Table Size Width..... 17-1/4 in.
 Table Size Thickness..... 1-1/2 in.
 Floor To Cutting Area Height..... 37-1/2 in.

Other Specifications:

Country Of Origin Taiwan
 Warranty 1 Year
 Serial Number Location ID Label on Center of Upper Wheel Cover
 Assembly Time 1 hour
 Sound Rating 78 dB