

Grizzly[®] Industrial

CORPORATE HEADQUARTERS

P.O. BOX 2069, BELLINGHAM, WA, U.S.A.

TELEPHONE: (360) 647-0801 • FAX: (360) 676-1075

Introducing the Grizzly Model G1030Z2 3HP Dust Collector



MADE IN AN
ISO 9001
FACTORY

MACHINE HIGHLIGHTS (see *Machine Data Sheet* for full specifications)

- 3 HP, 220V, single-phase motor.
- Maximum air suction capacity of 2,300 CFM with a maximum static pressure of 16.7".
- Improved 12³/₄" balanced steel impeller with radial fins.
- Features two 2.5 micron upper filtration bags and two 11.4 cu. ft. disposable collection bags.
- 7" main inlet has removable Y-fitting with three 4" openings for capturing dust from multiple machines.
- Powder-coated steel stand with four plastic casters ensures full mobility—weighs 170 lbs.

The Model G1030Z2 is available for \$450.00. As with all Grizzly products, the Model G1030Z2 is covered by a one-year warranty. For more information call 1-800-523-4777 or visit www.grizzly.com.



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1030Z2 3 HP DUST COLLECTOR WITH NEW IMPELLER

Product Dimensions:

Weight..... 156 lbs.
 Length/Width/Height..... 49-1/2 x 21-1/2 x 78 in.
 Foot Print (Length/Width)..... 49-1/2 x 21-1/2 in.

Shipping Dimensions:

Type..... Cardboard
 Content..... Machine
 Weight..... 170 lbs.
 Length/Width/Height..... 51 x 22 x 23 in.

Electrical:

Minimum Circuit Size..... 30 amp
 Switch..... On/Off Push Button
 Switch Voltage..... 220V
 Cord Length..... 6 ft.
 Cord Gauge..... 14 gauge
 Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
 Horsepower..... 3
 Voltage..... 220V
 Prewired..... 220V
 Phase..... Single
 Amps..... 18
 Speed..... 3450
 Cycle..... 60 Hz
 Number Of Speeds..... 1
 Power Transfer Direct Drive
 Bearings..... Sealed and Lubricated for Life

Main Specifications:

Operation

Air Suction Cap..... 2300 CFM
 Maximum Static Pressure..... 16.7 in.
 Main Inlet Size..... 7 in.
 Manifold Included..... Yes
 Manifold Inlets..... 3
 Manifold Inlet Size..... 4 in.
 Machine Collection Cap..... 3
 Maximum Material Collection Cap..... 11.4 cu. ft.
 Upper Bag Filtration..... 2.5 micron

Bag Information

No Of Upper Bags.....	2
Upper Bag Cap.....	5.7 cu. ft.
Lower Bag Cap.....	5.7 cu. ft.
No Of Lower Bags.....	2
Upper Bags Total Area.....	11.4 cu. ft.
Lower Bags Total Area.....	11.4 cu. ft.
Upper Bag Diameter.....	19-1/2 in.
Upper Bag Length.....	33 in.
Lower Bag Diameter.....	19-1/2 in.
Lower Bag Length.....	33 in.

Impeller Information

Impeller Type.....	Radial Fin
Impeller Size.....	12-3/4 in.
Impeller Blade Thickness.....	1/8 in.

Construction

Upper Bag Material.....	Fabric
Lower Bag Material.....	Plastic
Base Construction.....	Fabricated Sheet Metal with Casters
Frame Construction.....	Formed Steel
Caster Construction.....	High Density Plastic
Impeller Construction.....	Balanced Steel, Riveted Fins
Paint.....	Powder Coated

Other

Height With Bags Inflated.....	78 in.
--------------------------------	--------

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Machine Label Above Magnetic On/OFF Switch
Awards	Wood Magazine Top Value 1997
Assembly Time	1 Hour

Features:

- Fully Mobile
- Powder Coated Paint
- Includes Steel Base with Casters