



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G9922 OSCILLATING SPINDLE SANDER

### Product Dimensions:

Weight..... 86 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 26 x 26 x 39-1/2 in.  
Footprint (Length x Width)..... 25-1/2 x 25 in.

### Shipping Dimensions:

Type..... Cardboard Box  
Content..... Machine  
Weight..... 102 lbs.  
Length x Width x Height..... 18 x 17 x 23 in.  
Must Ship Upright..... No

### Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 4.6A  
Minimum Circuit Size..... 15A  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 18 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-15  
Switch Type..... Paddle Safety Switch w/Removable Key

### Motors:

#### Main

Horsepower..... 1/2 HP  
Phase..... Single-Phase  
Amps..... 4.6A  
Speed..... 3450 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Direct Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

### Main Specifications:

**Spindle Sander Info**

Sanding Drum Diameters.....	2 in.
Sanding Drum Length.....	5-1/2 in.
Spindle Speed.....	3450 RPM
Spindle Oscillation.....	64 SPM
Stroke Length.....	1 in.
Table Length.....	14-1/2 in.
Table Width.....	14-1/2 in.
Table Thickness.....	1 in.
Table-to-Floor Height.....	39-1/2 in.
Number of Table Inserts.....	1
Included Sanding Sleeve Grit Size.....	80
Table Tilt.....	Left 0, Right 45 deg.

**Construction Materials**

Base.....	Formed Steel
Stand.....	Steel
Table.....	Ground Cast Iron
Frame.....	Steel
Miter Gauge.....	Plastic
Paint Type/Finish.....	Epoxy

**Other Related Info**

Miter Gauge Slot Width.....	5/8 in.
Miter Gauge Slot Height.....	1/4 in.
Number of Dust Ports.....	1
Dust Port Size.....	2 in.
Compatible Mobile Base.....	D2057A

**Other Specifications:**

Country of Origin .....	China
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	ID Label
ISO 9001 Factory .....	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	No

**Features:**

- Includes 80 Grit Sanding Sleeve, Miter Gauge and Wrench Set
- Table Tilts to 45 deg. for Bevel Sanding
- Steel Construction
- Cast-Iron Table
- Paddle Safety Switch with Lock